

Cisco Wireless Ordering Guide

Contents

Cisco wireless access point product family	3
Cisco Catalyst and Cisco Wireless 9100 indoor access points ordering steps	6
Cisco Catalyst 9100 Outdoor Access Points ordering steps	11
Cisco Networking Subscription overview	16
Cisco platforms supported by unified licensing	16
How to order a Cisco Networking Subscription	17
Cisco DNA software for wireless product overview	22
Cisco Catalyst 9800 Series highlights	25
Wireless platform support summary and part numbers	26
Cisco Catalyst 9800 Series Wireless Controller ordering steps	28
Licensing	42
Additional information	44
Cisco Software-Defined Access (SD-Access)	45
Services	45
Important links	46

Cisco wireless access point product family

Ordering information

Tables 1 through 4 provide ordering information for the Cisco® wireless access points. To place an order, visit the [Cisco Ordering homepage](#). To download software, visit the [Cisco Software Center](#).

Note:

- Beginning with Wi-Fi 7 products (currently, the 9178, 9176, and 9172 Series), Cisco Wireless access points are global use access points. This means that you are no longer required to order using regulatory domain codes or management mode-specific part numbers. Global use access points automatically onboard to the network management mode of choice, determining the physical locality upon install. Information on licensing for Wi-Fi 7 products is in Table 6.
- Customers are responsible for verifying approval for use in their individual countries. To verify approval that corresponds to a particular country, or the regulatory domain used in a specific country, visit <https://www.cisco.com/go/compliance>.
- Regulatory domain approval occurs in phases. As they are approved, the part numbers will be available on the Cisco Global Price List (GPL).
- Regulatory domains: (x=regulatory domain).
- When ordering the Cisco Catalyst 9166, 9164 and 9162 Series Access Points, a choice must be made on AP deployment/management. For on-premises management -x part number should be ordered, for cloud use -MR.

Table 1. Indoor access points

Product name	Part number	Description
Cisco Wireless 9178 Series	CW9178I	Cisco Wireless 9178I Access Point, Wi-Fi 7, internal omnidirectional antennas, quad client-serving radios, tri-band with 4x4:4 on all radios, up to 16 spatial streams, dual 5 GHz, 10G mGig, Integrated GNSS/GPS, UWB. Global Use
Cisco Wireless 9176 Series	CW9176I	Cisco Wireless 9176I Access Point, Wi-Fi 7, internal omnidirectional antennas, tri-band, 12 spatial streams with 4x4:4 on all radios. Operates in either 2/5/6 mode or 5/5/6 mode. 10G mGig, Integrated GNSS/GPS, UWB. Global Use.
	CW9176D1	Cisco Wireless 9176I Access Point, Wi-Fi 7, internal directional antennas, tri-band, 12 spatial streams with 4x4:4 on all radios. Operates in either 2/5/6 mode or 5/5/6 mode. 10G mGig, Integrated GNSS/GPS, UWB. Global Use.
Cisco Wireless 9172 Series	CW9172H	Cisco Wireless 9172H Access Point, Wi-Fi 7, internal omnidirectional antennas, tri-band, 6 spatial streams with 2x2:2 on all radios. 2.5G mGig with multiple LAN ports (3x 1Gbps LAN, and 1 passthrough port) and PoE out support. Global Use.
	CW9172I	Cisco Wireless 9172I Access Point, Wi-Fi 7, internal omnidirectional antennas, tri-radio or dual-radio operation, 6 spatial streams with 2x2:2 across all radios, or 2x2:2 on 2.4GHz and 4x4:4 on 5GHz with 6GHz disabled. 2.5G mGig, USB 2.0, and a DC power jack. Global Use.

Product name	Part number	Description
Cisco Catalyst™ 9166 Series	CW9166I-x	Cisco Catalyst 9166I Access Point, Wi-Fi 6E, internal antennas, 4x4+4x4+4x4 MIMO with XOR radio, 5G mGig with Reg-X.
	CW9166I-MR	Cisco Catalyst 9166I Access Point, Wi-Fi 6E, internal antennas, 4x4+4x4+4x4 MIMO with XOR radio, 5G mGig with Meraki.
	CW9166D1-x	Cisco Catalyst 9166 Series Access Point, integrated directional antennas, 4x4+4x4+4x4 MIMO with XOR radio, 5G mGig with Reg-X
	CW9166D1-MR	Cisco Catalyst 9166 Series Access Point, integrated directional antennas, 4x4+4x4+4x4 MIMO with XOR radio, 5G mGig with Meraki
	Note: Customers ordering 9160 Access Points shipping with Meraki Management Mode (-MR) must have a Meraki license to operate with the Meraki dashboard or to migrate to Cisco DNA Management Mode.	
Cisco Catalyst 9164 Series	CW9164I-x	Cisco Catalyst 9164I Access Point, Wi-Fi 6E, internal antennas, 2x2+4x4+4x4 MIMO, 2.5G mGig with Reg-X.
	CW9164I-MR	Cisco Catalyst 9164I Access Point, Wi-Fi 6E, internal antennas, 2x2+4x4+4x4 MIMO, 2.5G mGig with Meraki.
	Note: Customers ordering 9160 Access Point shipping with Meraki Management Mode (-MR) must have a Meraki license to operate with the Meraki dashboard or to migrate to Cisco DNA Management Mode.	
Cisco Catalyst 9162 Series	CW9162I-x	Cisco Catalyst 9162I Access Point, Wi-Fi 6E, internal antennas, 2x2+2x2+2x2 MIMO, 2.5G mGig with Reg-X.
	CW9162I-MR	Cisco Catalyst 9162I Access Point, Wi-Fi 6E, internal antennas, 2x2+2x2+2x2 MIMO, 2.5G mGig with Meraki.
	Note: Customers ordering 9160 Access Points shipping with Meraki Management Mode (-MR) must have a Meraki license to operate with the Meraki dashboard or to migrate to Cisco DNA Management Mode.	
Cisco Catalyst 9136 Series	C9136I-x	Cisco Catalyst 9136I Access Point, Wi-Fi 6E, internal antennas, 4x4+8x8+4x4 MIMO
Cisco Catalyst 9130AX Series	C9130AXI-x	Cisco Catalyst 9130AXI Access Point, internal antennas; 802.11ax; 8x8:8 MIMO
	C9130AXE-x	Cisco Catalyst 9130AXE Access Point, external antennas; 802.11ax; 8x8:8 MIMO
	C9130AXE-STA-x	Cisco Catalyst 9130AXE Stadium Antenna Access Point, external antennas (C-ANT9104); 802.11ax; dual 5 GHz MIMO
Cisco Catalyst 9120AX Series	C9120AXI-x	Cisco Catalyst 9120AXI Access Point, internal antennas; Wi-Fi 6; 4x4:4 MIMO
	C9120AXE-x	Cisco Catalyst 9120AXE Access Point, external antennas; Wi-Fi 6; 4x4:4 MIMO
	C9120AXP-x	Cisco Catalyst 9120AXP Access Point, external antennas; professional install; Wi-Fi 6; 4x4:4 MIMO

Product name	Part number	Description
Cisco Catalyst 9115AX Series	C9115AXI-x	Cisco Catalyst 9115AXI Access Point, internal antenna; Wi-Fi 6; 4x4:4 MIMO
	C9115AXE-x	Cisco Catalyst 9115AXE Access Point, external antenna; Wi-Fi 6; 4x4:4 MIMO
Cisco Catalyst 9105AX Series	C9105AXI-x	Cisco Catalyst 9105AX Access Point, internal antenna; ceiling mount, Wi-Fi 6; 2x2:2 MIMO
	C9105AXW-x	Cisco Catalyst 9105AX Access Point, internal antenna; wall mount, Wi-Fi 6; 2x2:2 MIMO

Table 2. Outdoor access points

Product name	Part number	Description
Cisco Catalyst 9163E Series	CW9163E-x	Cisco Catalyst 9163E Outdoor Access Point, N-type antenna connectors; Wi-Fi 6E; 2x2:2SS with Reg X
	CW9163E-MR	Cisco Catalyst 9163E Outdoor Access Point, N-type antenna connectors; Wi-Fi 6E; 2x2:2SS with Meraki
Cisco Catalyst 9124AX Series	C9124AXI-x	Cisco Catalyst 9124AX Outdoor Access Point, internal omnidirectional antenna; Wi-Fi 6; 4x4:4 MIMO
	C9124AXD-x	Cisco Catalyst 9124AX Outdoor Access Point, internal directional antenna; Wi-Fi 6; 4x4:4 MIMO
	C9124AXE-x	Cisco Catalyst 9124AX Outdoor Access Point, external omnidirectional antenna; Wi-Fi 6; 4x4:4 MIMO

Note: “x” is a placeholder for the regulatory domain designator. Visit <https://www.cisco.com/go/aironet/compliance> to determine which regulatory domain is used in your country. The regulatory domain used in your country may differ depending on access point model, and some models are not available for all countries. Regulatory domains are not required when ordering Wi-Fi 7 (currently, the 9178, 9176, and 9172 Series) access points.

Cisco Catalyst and Cisco Wireless 9100 indoor access points ordering steps

Select the access point model based on requirements and as per the correct country's regulatory domain.

Table 3. 9100 access points

AP part number	Description
CW9178I	Cisco Wireless 9178I Access Point, Wi-Fi 7, internal antennas, quad client-serving radios, tri-band with 4x4:4 on all radios, up to 16 spatial streams, dual 5 GHz, 10G mGig, Integrated GNSS/GPS, UWB. Global Use
CW9176I	Cisco Wireless 9176I Access Point, Wi-Fi 7, internal omni directional antennas, tri-band, 12 spatial streams with 4x4:4 on all radios. Operates in either 2/5/6 mode or 5/5/6 mode. 10G mGig, Integrated GNSS/GPS, UWB. Global Use.
CW9176D1	Cisco Wireless 9176D1 Access Point, Wi-Fi 7, internal directional antennas, tri-band, 12 spatial streams with 4x4:4 on all radios. Operates in either 2/5/6 mode or 5/5/6 mode. 10G mGig, Integrated GNSS/GPS, UWB. Global Use.
CW9172H	Cisco Wireless 9172H Access Point, Wi-Fi 7, internal omni-directional antennas, tri-radio, 6 spatial streams with 2x2:2 on all radios. 2.5Gbps uplink, 3x 1Gbps LAN ports with PoE out, 1 passthrough port. Integrated BLE and 802.15.4 for IoT. Compact, energy-efficient design. Global Use.
CW9172I	Cisco Wireless 9172I Access Point, Wi-Fi 7, internal omni-directional antennas, tri-radio or dual-radio, 6 spatial streams with 2x2:2 on 2.4GHz, 5GHz, and 6GHz, or 2x2:2 on 2.4GHz and 4x4:4 on 5GHz with 6GHz disabled. 2.5Gbps uplink, USB 2.0, DC power jack. Integrated BLE and 802.15.4 for IoT. Energy-efficient operation. Global Use.
CW9166I-X	Cisco Catalyst 9166I Access Point, Wi-Fi 6E, internal antennas, 4x4+4x4+4x4 MIMO with XOR radio, 5G mGig with Reg-X
CW9166I-MR	Cisco Catalyst 9166I Access Point, Wi-Fi 6E, internal antennas, 4x4+4x4+4x4 MIMO with XOR radio, 5G mGig with Meraki Note: Customers ordering 9160 access points shipping with Meraki Management Mode (-MR) must have a Meraki license to operate with the Meraki dashboard or to migrate to Cisco DNA Management Mode.
CW9166D1-X	Cisco Catalyst 9166DI Access Point, Wi-Fi 6E, integrated directional antenna, 4x4+4x4+4x4 MIMO with XOR radio, 5G mGig, with Reg-X.
CW9166D1-MR	Cisco Catalyst 9166DI Access Point, Wi-Fi 6E, integrated directional antenna, 4x4+4x4+4x4 MIMO with XOR radio, 5G mGig, with Meraki. Note: Customers ordering 916X access points shipping with Meraki Management Mode (-MR) must have a Meraki license to operate with the Meraki dashboard or to migrate to Cisco DNA Management Mode.
CW9164I-X	Cisco Catalyst 9164I Access Point, Wi-Fi 6E, internal antennas, 2x2+4x4+4x4 MIMO, 2.5G mGig with Reg-X.
CW9164I-MR	Cisco Catalyst 9164I Access Point, Wi-Fi 6E, internal antennas, 2x2+4x4+4x4 MIMO, 2.5G mGig with Meraki. Note: Customers ordering 9160 access points shipping with Meraki Management Mode (-MR) must have a Meraki license to operate with the Meraki dashboard or to migrate to Cisco DNA Management Mode.
CW9162I-x	Cisco Catalyst 9162I Access Point, Wi-Fi 6E, internal antennas, 2x2+2x2+2x2 MIMO, 2.5G mGig with Reg-X.

AP part number	Description
CW9162I-MR	Cisco Catalyst 9162I Access Point, Wi-Fi 6E, internal antennas, 2x2+2x2+2x2 MIMO, 2.5G mGig with Meraki. Note: Customers ordering 9160 access points shipping with Meraki Management Mode (-MR) must have a Meraki license to operate with the Meraki dashboard or to migrate to Cisco DNA Management Mode.
C9136I-x	Cisco Catalyst 9136I Access Point, Wi-Fi 6E, internal antennas, 4x4+8x8+4x4 MIMO
C9130AXI-x	Cisco Catalyst 9130AXI Access Point, internal antennas; 802.11ax; 8x8:8 MIMO
C9130AXE-x	Cisco Catalyst 9130AXE Access Point, external antennas; 802.11ax; 8x8:8 MIMO
C9130AXE-STA-x	Cisco Catalyst 9130AXE Access Point, C-9104 Stadium Antenna; 802.11ax; Dual 5 GHz MIMO
C9120AXI-x	Cisco Catalyst 9120AXI Access Point, internal antennas; Wi-Fi 6; 4x4:4 MIMO
C9120AXE-x	Cisco Catalyst 9120AXE Access Point, external antennas; Wi-Fi 6; 4x4:4 MIMO
C9120AXP-x	Cisco Catalyst 9120AXP Access Point, external antennas; professional install; Wi-Fi 6; 4x4:4 MIMO
C9115AXI-x	Cisco Catalyst 9115AXI Access Point, internal antenna; Wi-Fi 6; 4x4:4 MIMO
C9115AXE-x	Cisco Catalyst 9115AXE Access Point, external antenna; Wi-Fi 6; 4x4:4 MIMO
C9105AXI-x	Cisco Catalyst 9105AX Access Point, internal antenna; ceiling mount, Wi-Fi 6; 2x2:2 MIMO
C9105AXW-x	Cisco Catalyst 9105AX Access Point, internal antenna; wall mount, Wi-Fi 6; 2x2:2 MIMO

Note: When ordering the Cisco Catalyst 9166, 9166D1, 9164, or 9162 access point, a choice must be made on AP deployment/management. For on-premises management -x part number should be ordered, for cloud use -MR.

Note: When customers order the Cisco Catalyst 9130AXE Access Point, the following instructions need to be adhered to:

Note: Customer either has to order new cables and bracket (see below) and use current antennas:

Table 4. Antenna connector and brackets

AP part number	Description
AIR-CAB002-D8-R=	8-Port Smart antenna connector to RP-TNC connectors, 2ft
AIR-CAB003-D8-N=	8-Port Smart antenna connector to N-Type connectors, 3ft

Or purchase one of the newly released 8x8 antennas, which has the DART cables attached, and bracket:

Table 5. 8-Port antenna and brackets

AP part number	Description
C-ANT9101=	2.4/5/6 GHz Ceiling mount omni antenna, 8-port, DART, Self ID
C-ANT9102=	2.4/5/6 GHz Multi mount omni antenna, 8-port, DART, Self ID
C-ANT9103=	2.4/5/6 GHz Directional antenna, 8-port, DART, Self ID
AIR-AP-BRACKET-9=	C9130AXE antenna bracket

For ordering of Cisco Wireless Wi-Fi 7 products – currently the 9178, 9176, 9172 Series – unified licenses are available for purchase regardless of management or deployment type, within a Cisco Networking Subscription.

Table 6. Unified licenses available in the Cisco Networking Subscription

Cisco part number	Description
LIC-CW-E	Cisco Wireless Essentials
LIC-CW-A	Cisco Wireless Advantage

Cisco DNA licenses are required when using Wi-Fi 6 and Wi-Fi 6E APs with the Catalyst 9800 Series Controllers and Cisco Catalyst Center. Select your required Cisco DNA license and subscription duration from the following licensing tier options:

- Essentials (-E) - AIR-DNA-E
- Advantage (-A) - AIR-DNA-A

When ordering all other Catalyst 9100 access points, except for the new Wi-Fi 7 global use access points, one of the following Cisco DNA options must be selected in 3-year, 5-year, or 7-year subscription terms:

Table 7. Cisco DNA Subscription

Cisco DNA part number	Subscription option	Description
AIR-DNA-E	AIR-DNA-E-3Y	Cisco DNA Essentials license with 3-year subscription
	AIR-DNA-E-5Y	Cisco DNA Essentials license with 5-year subscription
	AIR-DNA-E-7Y	Cisco DNA Essentials license with 7-year subscription
AIR-DNA-A	AIR-DNA-A-3Y	Cisco DNA Advantage license with 3-year subscription
	AIR-DNA-A-5Y*	Cisco DNA Advantage license with 5-year subscription (default option)
	AIR-DNA-A-7Y	Cisco DNA Advantage license with 7-year subscription

* **Note:** AIR-DNA Advantage with a 5-year subscription option is selected by default.

Note: For ordering and use of Cisco Wireless Wi-Fi 7 products unified licenses, rather than either DNA or Meraki licensing, are eligible for purchase. See Table 6 for ordering of the new Cisco Networking Subscription part numbers.

Select 2.4/5 GHz dual-band external antennas (applicable if the external antenna version of the access point is selected):

Table 8. External antennas

Antenna part number	Description
AIR-ANT2524DW-RS	Cisco Aironet dual-band dipole antenna; white; peak gain 2dBi at 2.4 GHz and 5 dBi at 5 GHz
AIR-ANT2535SDW-RS	Cisco Aironet short dual-band omni antenna, Peak Gain 3 dBi at 2.4. GHz and 5 dBi at 5 GHz
AIR-ANT2524V4C-RS=	Cisco Aironet omni antenna, ceiling mount, Peak Gain 2 dBi at 2.4. GHz and 4 dBi at 5 GHz
AIR-ANT2544V4M-RS=	Cisco Aironet omni antenna, wall/pole mount, Peak Gain 2 dBi at 2.4 GHz and 4 dBi at 5 GHz
AIR-ANT2566P4W-RS=	Cisco Aironet patch antenna, wall/pole mount, Peak Gain 6 dBi at 2.4 GHz and 6 dBi at 5 GHz
AIR-ANT2566D4M-RS=	Cisco Aironet directional antenna, wall/pole mount, Peak Gain 6 dBi at 2.4 GHz and 6 dBi at 5 GHz
AIR-ANT2513P4M-NS=	Cisco Aironet directional antenna, wall/pole mount, Peak Gain 13 dBi at 2.4 GHz and 13 dBi at 5 GHz
AIR-ANT2566P4W-DS=	Cisco Aironet patch antenna, wall/pole mount, Peak Gain 6 dBi at 2.4 GHz and 6 dBi at 5 GHz, 4-port DART connector
AIR-ANT2566D4M-DS=	Cisco Aironet directional antenna, wall/pole mount, Peak Gain 6 dBi at 2.4 GHz and 6 dBi at 5 GHz, 4-port DART connector

Select access point mounting brackets:

Table 9. Mounting brackets

Part number	Description
AIR-AP-NO BRACKET	Select this option if no bracket is required
AIR-AP-BRACKET-1	Low-profile access point mounting bracket, default option
AIR-AP-BRACKET-2	Universal bracket for access point mounting
AIR-AP-BRACKET-W4	Bracket for Cisco Catalyst 9105w access point mounting
AIR-AP-BRACKET-8	Bracket for Cisco Catalyst 9105i access point mounting
CW-MNT-ART2-00	Articulating arm for bracket 2
CW-MNT-H1	Bracket for Cisco Wireless 9172H access point mounting
CW-MNT-H3	Bracket for Cisco Wireless 9172H access point mounting with LAN port security
CW-ACC-SPACER1	Wall spacer accessory for Cisco Wireless 9172H access point
CW-ACC-DESK1	Desk top stand accessory for Cisco Wireless 9172H access point

Select ceiling grid clips:

Table 10. Ceiling grid clips

Part number	Description
AIR-AP-T-RAIL-R	Ceiling grid clip (recessed mounting); this is the default option
AIR-AP-T-RAIL-F	Ceiling grid clip (flush mounting)
AIR-CHNL-ADAPTER	Optional adapter for channel-rail ceiling grid profile

Select the access point powering options (to be ordered separately):

Table 11. Powering options

Source	Description
CW-INJ-8	802.3bt, 60W, Cisco Power Injector, 10 Gbps Ethernet
AIR-PWRINJ7=	802.3bt Cisco Power Injector, 5Gbps Ethernet
AIR-PWRINJ6=	802.3at Cisco Power Injector
PoE+ via switch port	Any 802.3at (30.0 W) compliant switch port

Note: Please check access point data sheets for power requirements. In some applications, if AIR-PWRINJ6 is used the access point will work with reduced features. For more details, refer to the respective access point data sheet.

For APs with integrated GNSS/GPS receivers and antennas, the following optional external GNSS antennas are available for deployments where the antenna cannot be co-located with the AP.

Table 12. GNSS connector

Source	Description
CW-ANT-GPS1-M-00	GNSS antenna, MMCX connector, 10m

For APs that do not have integrated GNSS/GPS receivers, the following module is available. Supported on CW916x series indoor APs.

Table 13. GPS/GNSS Module USB

Source	Description
CW-ACC-GPS1=	Catalyst Wireless GPS/GNSS Module, USB

Cisco Catalyst 9100 Outdoor Access Points ordering steps

Select the access point model based on requirements and as per the correct country's regulatory domain.

Table 14. Access points

AP part number	Description
CW9163E-x	Cisco Catalyst 9163E Outdoor Access Point, N-type antenna connectors; Wi-Fi 6E; 2x2:2SS with Reg -x
CW9163E-MR	Cisco Catalyst 9163E Outdoor Access Point, N-type antenna connectors; Wi-Fi 6E; 2x2:2SS with Reg -MR
C9124AXI-x	Cisco Catalyst 9124AX Outdoor Access Point, internal omnidirectional antenna; Wi-Fi 6; 4x4:4 MIMO
C9124AXD-x	Cisco Catalyst 9124AX Outdoor Access Point, internal directional antenna; Wi-Fi 6; 4x4:4 MIMO
C9124AXE-x	Cisco Catalyst 9124AX Outdoor Access Point, external antenna; Wi-Fi 6; 4x4:4 MIMO

Note: When customers order a Cisco Catalyst 9124AX Series Access Point, the following instructions need to be adhered to.

Note: Some components are available as a “configurable” option or as a “spare.”

- A “configurable” option ships in the same main box as the access point. For example, AIR-MNT-VERT1 is a “configurable” option and, if ordered, is shipped with the access point in the same box.
- A “spare” option is denoted with an equal (=) sign at the end of the part number. For example, AIR-MNT-ART1 = is a “spare” and, if ordered, is shipped in separate packaging.

Select appropriate software:

Table 15. Software

Software part number	Description
SW9124AX-CAPWAP-K9	CAPWAP software
SW9124AX-MESH-K9	Mesh software for C9124AXI/D
SW9124AXE-CW-K9	CAPWAP software for C9124AXE
SW9124AXE-MESH-K9	MESH software for C9124AXE

Cisco DNA software licenses are required when using Wi-Fi 6 and Wi-Fi 6E APs with the Catalyst 9800 Series wireless controllers and Cisco Catalyst Center (previously Cisco DNA Center). Select your required Cisco DNA license and subscription duration from the following licensing tier options:

- Essentials (-E) - AIR-DNA-E
- Advantage (-A) - AIR-DNA-A

When ordering the Catalyst 9100, one of the following Cisco DNA options must be selected in 3-year, 5-year, or 7-year subscription terms:

Table 16. Cisco DNA Subscription

Cisco part number	Subscription option	Description
AIR-DNA-E	AIR-DNA-E-3Y	Cisco DNA Essentials license with 3-year subscription
	AIR-DNA-E-5Y	Cisco DNA Essentials license with 5-year subscription
	AIR-DNA-E-7Y	Cisco DNA Essentials license with 7-year subscription
AIR-DNA-A	AIR-DNA-A-3Y	Cisco DNA Advantage license with 3-year subscription
	AIR-DNA-A-5Y*	Cisco DNA Advantage license with 5-year subscription (default option)
	AIR-DNA-A-7Y	Cisco DNA Advantage license with 7-year subscription

* **Note:** AIR-DNA Advantage with a 5-year subscription option is selected by default.

Select 2.4- and 5-GHz dual-band external antennas (applicable if the external antenna version of the access point is selected).

Table 17. External configurable antennas

Part number	Generation	Qty	Description
AIR-ANT2568VG-NS	SIA	4	2.4GHz 6dBi / 5GHz 8dBi Omnidirectional Antenna, Connectors N-Male
AIR-ANT2547VG-NS	SIA	4	2.4GHz 4dBi / 5GHz 7dBi Omnidirectional Colinear Array Antenna, Connectors N-Male

Table 18. External spare antennas

Part number	Generation	Qty	Description
CW-ANT-O1-NS-00	SIA	1	External omni-directional antenna for CW9163E; Wi-Fi 6E; 2x2:2SS, Four (4) antennas required to fully populate antenna ports on CW9163E
CW-ANT-GPS2-S-00	SIA	1	External GPS Antenna for CW9163E; Wi-Fi 6E; 2x2:2SS
CW-ANT-D1-NS-00	SIA	1	External 4-Port Directional Patch Self-Identifying Antenna (SIA) with N-Type Connectors, includes CW-MNT-ART2-00, articulating arm bracket
AIR-ANT2568VG-NS=	SIA	4	2.4GHz 6dBi / 5GHz 8dBi Omnidirectional Antenna, Connectors N-Male

Part number	Generation	Qty	Description
AIR-ANT2547VG-NS=	SIA	4	2.4GHz 4dBi / 5GHz 7dBi Omnidirectional Colinear Array Antenna, Connectors N-Male
AIR-ANT2588P4M-NS=	SIA	1	2.4GHz 8dBi / 5GHz 8dBi 4-Element Dual-Polarized Patch Antenna, Connectors N-Female Bulkhead (4x RF Coaxial Cable needed)
AIR-ANT2513P4M-NS=	SIA	1	2.4GHz 13dBi / 5GHz 13dBi Dual-Band Polarization Diverse Patch Array Antenna, Connectors N-Female Bulkhead (4x RF Coaxial Cable needed)
AIR-ANT2547V-N=	Legacy	4	2.4GHz 4dBi / 5GHz 7dBi Omnidirectional Colinear Array Antenna, Connectors N-Male
AIR-ANT2547VG-N=	Legacy	4	2.4GHz 4dBi / 5GHz 7dBi Omnidirectional Colinear Array Antenna, Connectors N-Male (Grey Color)
AIR-ANT2450V-N=	Legacy	4	2.4GHz 5dBi Omnidirectional Colinear Array Antenna, Connectors N-Male
AIR-ANT2480V-N=	Legacy	4	2.4GHz 8dBi Omnidirectional Colinear Array Antenna, Connectors N-Male
AIR-ANT5180V-N=	Legacy	4	5GHz 8dBi 2-Element Omnidirectional Colinear Array Antenna, Connectors N-Male
AIR-ANT2513P4M-N=	Legacy	1	2.4GHz 13dBi / 5GHz 13dBi Dual-Band Polarization Diverse Patch Array Antenna, Connectors N-Female Bulkhead (4x RF Coaxial Cable needed)

Note:

- The Catalyst 9124AXI access point has four internal dual-band (2.4- and 5-GHz) antennas that reside under a sealed radome and cannot be accessed.
- The Catalyst 9124AXD access point has four internal directional dual-band (2.4- and 5-GHz) antennas that reside under a sealed radome and cannot be accessed.

Select the access point RF cables and lightning arrestor (to be ordered separately when remote antennas are connected, as per the requirement).

Table 19. RF cables and lightning arrestor

Part number	Description
AIR-CAB005LL-N=	RF Cable, 5 ft Low-loss, N Connectors
AIR-CAB010LL-N=	RF Cable, 10 ft Low-loss, N Connectors
AIR-ACC245LA-N	Lightning Arrestor (If C9124AXE is connected to remote antenna through cable)

Select the access point powering options (to be ordered separately, as per the requirement). The Catalyst 9124AX Series Access Points can be powered by multiple sources: AC, DC, or Power over Ethernet (PoE). For AC powering, an external AC-to-DC power adapter is required. For DC powering, a 2-pin DC connector is included with every access point. The access point can also be powered by Cisco Universal Power over Ethernet (Cisco UPOE) or PoE+ (802.3at) directly from a switch or power injector.

Table 20. Powering options

Part number	Description	Use case
AIR-PWRINJ-60RGD1=	Power injector, 60W, outdoor, North America plug	Outdoor-rated 60W power injector with North American AC plug
AIR-PWRINJ-60RGD2=	Power injector, 60W, outdoor, un-connectorized	Outdoor-rated 60W power injector, unterminated AC cable for international use
AIR-PWRINJ-60-PMK=	Pole mount kit for AIR-PWRINJ-60	Required for pole mounting for AIR-PWRINJ-60RGD1= or AIR-PWRINJ-60RGD2=
AIR-PWRINJ6=	Power injector, 802.3at, indoor	Indoor-rated, 802.3at-compliant power injector

Note: Please check access point data sheets for power requirements. If AIR-PWRINJ6 is used, the access point will work with reduced features. For more details, refer to the respective access point data sheet.

Select the access point SFP options (to be ordered separately, as per the requirement).

Catalyst 9124AX Series outdoor access points support fiber backhaul. The SFP port is built into the access point, but the mechanical interface is external to the access point. A special SFP adapter/gland kit is needed to interface the fiber cable to the access point.

Table 21. SFP options

Adaptor Part number	Description	Use case
GLC-LX-SM-RGD	1000BASE-LX single-mode rugged SFP	Long-distance fiber backhaul on single-mode fiber
GLC-SX-MM-RGD	1000BASE-SX multi-mode rugged SFP	Shorter-distance fiber backhaul on multimode fiber
GLC-T-RGD	1000BASE-T SFP, industrial temp	GE electrical interface for bridging wired clients such as video cameras or switches

Select access point mounting brackets.

Table 22. Mounting brackets

Part number	Description
AIR-AP-NO-BRACKET	Select this option if no bracket is required
AIR-MNT-VERT1	Vertical mounting bracket for Cisco Catalyst 9124AXD access point, will be option in CCW
AIR-MNT-VERT1=	Vertical mounting bracket for Cisco Catalyst 9124AXD access point
AIR-MNT-ART1=	Articulating mounting bracket for Cisco Catalyst 9124AXD access point
AIR-MNT-HORZ1=	Horizontal mounting bracket for Cisco Catalyst 9124AXI/AXD access point
AIR-MNT-VERT2=	Vertical mounting bracket for Cisco Catalyst 9124AXD access point with AC/DC PSU

Part number	Description
AIR-MNT-STRAND1=	Strand mounting bracket for Cisco Catalyst 9124AXI/AXD access point

Select the access point powering options (to be ordered separately, as per the requirement).

Table 23. Accessories

Accessories Part number	Description
CW-ACC-KIT1-00	Accessory Kit for CW9163E
C9124-CVR1=	Paintable cover for Catalyst 9124AX
AIR-SFP-KIT1=	SFP installation kit for Catalyst 9124AX (QTY 5)
AIR-ACC-PS-MNT1=	AC/DC adapter mount bracket for AIR-MNT-HORZ1=
AIR-ACC-KIT1=	5x ethernet, 2 dust cap, ground lug, DC plug kit
AIR-ACC-CAT6=	CAT 6/6A Ethernet Cable Gland Assembly kit*

* **Note:** AIR-ACC-CAT6= is mandatory if C9124 is to be installed with Cat6/6a ethernet cable

Cisco Capital financing

Flexible payment solutions to help you achieve your objectives

The significant benefits offered by Cisco wireless access points make them the natural choice for providing best-in-class wireless connectivity. As with any technology investment, the question is the affordability of the new system. The answer is financing from Cisco Capital. Whether through flexible repayments to match expenditures to benefit and help mitigate cash flow issues, or an operating lease to help negate capital expenditure, we can give customers the financing solution that works best for them.

Cisco Capital can help remove or reduce the barriers preventing organizations from obtaining the technology they need. Total solution financing programs help customers and partners:

- Achieve business objectives
- Accelerate growth
- Acquire technology to match current strategies and future needs
- Remain competitive

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation, and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services, and complementary third-party equipment in easy, predictable payments. [Learn more](#).

Cisco Networking Subscription overview

The Cisco Networking Subscription streamlines the process of purchasing and using Cisco software, hardware, services, and platforms. This unified licensing model offers flexibility to manage your network on-premises, in the cloud, or hybrid.

You can purchase our new unified licenses (Cisco Wireless Essentials or Advantage) in a Cisco Networking subscription. These licenses include product support for both your hardware and software. With an active subscription, you can align renewal dates to your cost-center needs, add licenses without changing renewal dates, and upgrade entitlements midterm. The Cisco Networking Subscription provides flexible management options, supporting your network investment today and protecting it for the future.

For a full list of features in Cisco Wireless Essentials or Advantage, refer to the [Cisco Networking Subscription data sheet](#).

Cisco platforms supported by unified licensing

Unified licenses are compatible with the following:

Supported Access Points:

Cisco Wireless 9178 Series	CW9178I
Cisco Wireless 9176 Series	CW9176I, CW9176D1
Cisco Wireless 9172 Series	CW9172I, CW9172H

Supported Wireless LAN Controllers (WLCs):

Cisco 9800 Wireless LAN Controller Series	C9800-80-K9, C9800-40-K9, C9800-L-C-K9, C9800-L-F-K9, C9800-CL
Cisco CW9800 Wireless LAN Controller Series	CW9800H1, CW9800H2, CW9800M

Unified Licensing SKUs:

Cisco Wireless Essentials	LIC-CW-E
Cisco Wireless Advantage	LIC-CW-A

Firmware requirements:

- On-premises: IOS-XE 17.15.2
- Cloud: no Meraki firmware requirements

How to order a Cisco Networking Subscription

Step 1: In CCW, search for the desired Wi-Fi 7 device SKU, which will then take you through a “guided” buying experience.

The screenshot displays the Cisco Commerce Workspace (CCW) interface. At the top, there's a navigation bar with tabs: Catalog, Estimates, Deals & Quotes, Orders, Subscriptions & Services, and Software. Below this is a progress bar with steps: Catalog, Estimate Information, Items, and Install/Service. The main section is titled 'ESTIMATE NAME' and includes fields for Estimate ID, Created By, Created On, Intended Use (Internal Business Use), Customer Name (Cisco Systems, Inc.), and Price List (Global Price List Emerging (USD)).

The 'Items' section is active, showing a table of items. A dropdown menu is open for the 'CW9178' SKU, listing four options:

- CW9178-CFG: iGuide Me Wi-Fi 7, Cisco Wireless 9178 Access Point, Wi-Fi 7, Configurable. Catalyst 9168 Series Indoor Access Points.
- CW9178-CFG++: iGuide Me Wi-Fi 7, Cisco Wireless 9178 Access Point, Wi-Fi 7, Configurable. Catalyst 9168 Series Indoor Access Points.
- CW9178-CFG-T: Cisco Wireless 9178 Access Point, Wi-Fi 7, Configurable. Catalyst 9168 Series Indoor Access Points.
- CW9178-RTG: Wi-Fi 7 RTG. Catalyst 9168 Series Indoor Access Points.

The right sidebar shows a 'Financial summary with Hardware, Software and Services view'. It includes an 'Estimate Total' section with all prices at 0.00, and a 'Discounts' section with all discounts at 0%.

Step 2: If applicable, select the Wi-Fi 7 product series

The screenshot displays the Cisco Commerce Workspace (CCW) interface for the 'Choose the Product Series' step. The top navigation bar shows the product path: Cisco Wireless 9176: Wi-Fi 7, 3 rad... (Global Price List (USD) 0.00). The main section is titled 'Choose the Product Series' and shows two product series:

- CW9176I**: Best for traditional ceiling mounting with omni-directional coverage. (Selected)
- CW9176D1**: Best for deployments requiring directional antenna coverage. Wall or ceiling mount available.

The right sidebar shows a 'Configuration Summary' section with a table of products, quantities, and extended list prices. The table is currently empty, showing a shopping cart icon and the text 'No Configuration Price Items Added'.

Step 3: Select a device category:

- RTG: Ready to go – fastest shipment with default choices
- CFG: Configurable – customizable accessories and packaging
- Special Handling (CFG++) – use for TAA compliant orders

Cisco Wireless 9176: WiFi 7, 3 radio...
CW9176-WF17 NEW United States

Global Price List (USD) 0.00 Cancel Verify & Save

Product Series Device Category Model License Type Premium Support Co-Term Subscriptions Review

Choose Device Category [CW9176 Series]

Ready to Go

Fastest Shipment

- Includes Low Profile AP Mounting Bracket.
- Includes Ceiling Grid Clip: Recessed Mount.
- Single unit packaging.
- No customization.

Choose

Configurable

Customize accessories and packaging

- Single unit box or multi-unit packaging for easier unpacking and reduced cardboard waste.
- Allows selection of mounting brackets & ceiling rail clips.
- Option to not include brackets/clips to reduce waste.

Choose

Special Handling

Use for TAA compliant orders

- Ships with TAA-compliant Country of Origin.
- Single unit box or multi-unit packaging for easier unpacking and reduced cardboard waste.
- Allows selection of mounting brackets & ceiling rail clips.
- Option to include brackets/clips to reduce waste.

Choose

Back Continue

Summary Messages

Configuration Summary

Hide SD Items

PRODUCTS	QUANTITY	EXTENDED LIST PRICE
No Configuration Has Been Added		

Step 4a (Ready to Go): Select quantity of devices

Cisco Wireless 9176: WiFi 7, 3 radio...
CW9176-WF17 NEW United States

Global Price List (USD) Cancel Verify & Save

Product Series Device Category Model License Type Premium Support Co-Term Subscriptions Review

Enter Model Quantity

CW9176-WF17
CW9176i
Ready To Go

Cisco Wireless 9176i (WiFi 7, 3 radio, 3 band 4x4, 10W), Global

Unit List Price
Estimated Lead time: 0 days

10

Choose

Back Continue

Summary Messages

Configuration Summary

Hide SD Items

PRODUCTS	QUANTITY	EXTENDED LIST PRICE
HARDWARE		
CW9176i-RTG	10	

Step 4b (Configurable): Select quantity of devices, then choose from mounting bracket, ceiling clip, and packaging options

Cisco Wireless 9176: ...
CW9176-WF17 NEW United States

Global Price List (USD) Cancel Verify & Save

Product Series Device Category Model License Type Premium Support Co-Term Subscriptions Review

Cisco Wireless 9176D1 (WiFi 7, 3 radio, 3 band 4x4, 10W), Global

- For additional installation flexibility, the articulating mounting arm CW-MNT-ART2-00 can be added to the order as a separate line item after completing this workflow

Unit List Price
Estimated Lead time: 0 days

Choose

Choose a Mounting Bracket Option *

☐ No Bracket
 ☐ Universal AP Mounting Bracket

Choose a Ceiling Clip Option *

☐ No AP Ceiling Grid
 ☐ Ceiling Grid Clip: Recessed Mount
☐ Ceiling Grid Clip: Flush Mount
 ☐ Ceiling Grid Clip: T-Rail Channel Adapter

Choose a Packaging Option *

☐ Single Packaging
 ☐ Multi Packaging

Back Continue

Summary Messages

Configuration Summary

Hide SD Items

PRODUCTS	QUANTITY	EXTENDED LIST PRICE
HARDWARE		
CW9176D1-CFG	10	

Step 5: Select the desired product licensing model:

- Cisco Networking Subscription
- Meraki co-term licensing (co-term, cloud-only)
- Opt-out (hardware only)

Choose the Licensing Option

Cisco Networking Subscription

- Cisco Wireless license options.
- Common licenses for cloud-based or on-premises networks.

Meraki Co-Term Licensing

- For legacy Co-term/PDL customers.
- Selecting a Requested Start Date later than the hardware fulfillment date is recommended.

Opt-Out

- No License. Select this if you already have licenses for the APs or these APs will be used for sparring.

Configuration Summary

PRODUCTS	QUANTITY	EXTENDED LIST PRICE
HARDWARE		
CW9176-RTG	10	

If buying a Cisco Networking Subscription, continue with Step 6. Otherwise:

- **skip to Step 8 for Meraki Co-Term Licensing**
- **skip to Step 10 for Opt-Out**

Step 6: Select between Essentials or Advantage feature tier

Choose the License type

Essentials

- Licensing for basic or essential wireless network operation. For both cloud-based or on-premises networks.

Advantage

- Licensing with AI-powered features like AI-BSM, advanced security, and enhanced assurance.

Included Support

- Cisco Network Subscription licenses include: technical assistance (TAC) and Software Updates for issue resolution, digital insights, and e-Learning. More details can be found [here](#).

Add additional Cisco Networking Subscription licenses?

☐ Yes ☐ No

Configuration Summary

PRODUCTS	QUANTITY	EXTENDED LIST PRICE
HARDWARE		
CW9176-RTG	10	
SOFTWARE		
CSO-NETWORK-HUB	1	---
LIC-CW-E	10	---
LIC-SPACES-E	10	---
BVS-LISPT-CN	1	---

© 2013 Blackwell Publishing Ltd *Journal of Internal Medicine* 274: 103–112

Cisco Wireless 9176-WIFI 7, 3 rad...
CW9176-WIFI NEW United States

Global Price List (USD)

Cancel Verify & Save

Product Status

Device Category

Model

License Type

Product Support

Go To New Subscriptions

Remove

- Introducing the new cloud-based on-premises networks

- Introducing the new cloud-based on-premises networks

Included Support

- Cisco Network Subscription licenses include: technical assistance (TAC) and Software Updates for issue resolution, digital insights, and e-Learning. More details can be found here

Add additional Cisco Networking Subscription licenses?

☒ Yes ☐ No

Add additional licenses for your existing hardware

LIC-1200-E
Essentials

- Licensing for basic or essential wireless network operation. For both cloud-based or on-premises networks

LIC-1200-A
Advantage

- Licensing with AI-powered features like AI-RRM, advanced security, and enhanced assurance.

Summary

Messages

Configuration Summary

☒ View 2D View

PRODUCTS	QUANTITY	EXTENDED LIST PRICE
HARDWARE		
CW9176-470	10	
SOFTWARE		
CISCO-NETWORK-SUB	1	0.00
LIC-CW-1	10	
LIC-SPACES-1	10	

Step 8 (Meraki Co-Term Licensing): Select license option

Cisco Networking Subscription 9176: ...
CW9176-WIFI7 NEW United States

Global Price List (USD) Cancel Verify & Save ?

Product Series
Device Category
Model
License Type
Premium Support
Co-Term Subscriptions
Review

Choose the Licensing Option

Cisco Networking Subscription

- * Cisco Wireless license options.
- * Common licenses for cloud-based or on-premises networks.

Choose

Meraki Co-Term Licensing

- * For legacy Co-term/PDL customers.
- * Selecting a Requested Start Date later than the hardware fulfillment date is recommended.

Choose

Opt-Out

- * No License. Select this if you already have licenses for the APs or these APs will be used for sparing

Choose

Summary
Messages

Configuration Summary
Sort: Category

☐ Hide 50 Items

PRODUCTS	QUANTITY	EXTENDED LIST PRICE
HARDWARE		
CW9176D1-CFG C	10	
AIR-AP-BRACKET-2	10	0.00
AIR-AP-NO-CLIP	10	0.00
CW9176-MULTI PLN	10	0.00

Step 9 (Meraki Co-Term Licensing): Select license quantity



Cisco Wireless 9176: ...
CW9176-WIFI7 NEW United States

Global Price List (USD)
Cancel Verify & Save

Product Series
Device Category
Model
License Type
Premium Support
Review

Cisco Networking Subscription

- Cisco Wireless license options.
- Common licenses for cloud-based or on-premises networks.

Choose

Meraki Co-Term Licensing

- For legacy Co-term/PDL customers.
- Selecting a Requested Start Date later than the hardware fulfillment date is recommended.

Select

Opt-Out

- No License. Select this if you already have licenses for the APs or these APs will be used for sparing

Choose

Choose the License type

LIC-ENT-176
Meraki M9 Enterprise License, 176
Unit List Price

Choose

LIC-ENT-276
Meraki M9 Enterprise License, 276
Unit List Price

Choose

LIC-ENT-576
Meraki M9 Enterprise License, 576
Unit List Price

Choose

Summary
Messages

Configuration Summary

☐ Hide \$0 Items

PRODUCTS	QUANTITY	EXTENDED LIST PRICE
HARDWARE		
CW9176D1-CFG C	10	
AIR-AP-BRACKET-2	10	0.00
AIR-AP-NO-CLIP	10	0.00
CW9176-MULTI PUH	10	0.00

Step 10 (Opt-Out): Select license option

Cisco Wireless 9176: ...

CW9176-WIFI7

NEW

United States

Global Price List (USD)

Cancel

Verify & Save

Product Series

Device Category

Model

License Type

Premium Support

Co-Term Subscriptions

Review

Choose the Licensing Option

Reset Configuration

Cisco Networking Subscription

Cisco Wireless license options.
Common licenses for cloud-based or on-premises networks.

Choose

Meraki Co-Term Licensing

For legacy Co-term/PDL customers.
Selecting a Requested Start Date later than the hardware fulfillment date is recommended.

Choose

Opt-Out

No License. Select this if you already have licenses for the APs or these APs will be used for sparring

Choose

Summary

Messages

Configuration Summary

Hide 0 items

Sort: Category

PRODUCTS	QUANTITY	EXTENDED LIST PRICE
HARDWARE		
CW9176D1-RTG	10	

Step 11: Select optional RMA Upgrade options

Cisco Wireless 9176: WiFi 7, 3 rad...

CW9176-WIFI7

NEW

United States

Global Price List (USD)

Cancel

Verify & Save

Product Series

Device Category

Model

License Type

Premium Support

Co-Term Subscriptions

Review

What type of Support Upgrade do you want?

Reset Configuration

Opt-Out

RMA response based on Warranty terms

Choose

RMA ONLY EXTENDED

Next business day delivery, local business hours based on report time, 7 days a week

Choose

RMA ONLY 24X7X2

2-hour response, 24 hours a day, 7 days per week, including holidays

Choose

RMA ONLY 24X7X20H

2-hour response, 24 hours a day, 7 days per week, including holidays Onsite

Choose

RMA ONLY 24X7X4

4-hour response, 24 hours a day, 7 days a week, including holidays

Choose

RMA ONLY 24X7X8H

4-hour response, 24 hours a day, 7 days a week, including holidays Onsite

Choose

RMA ONLY EXTENDED

Next business day delivery, local business hours based on report time, 5 days a week

Choose

Summary

Messages

Configuration Summary

Hide 20 items

Sort: Category

PRODUCTS	QUANTITY	EXTENDED LIST PRICE
HARDWARE		
CW9176-RTG	10	
SOFTWARE		
CISCO-NETWORK-SUB	1	0.00
LC-CW-E	5	---
LC-CW-E	10	---
LC-SPACES-E	5	---
LC-SPACES-E	10	---

Step 12: Choose subscription details like renewal date and billing frequency

Cisco Wireless 9176: WiFi 7, 3 rad...

CW9176-WIFI7

NEW

United States

Global Price List (USD)

Cancel

Verify & Save

Product Series

Device Category

Model

License Type

Premium Support

Co-Term Subscriptions

Review

New Subscription Terms and Billing

Reset Configuration

Requested For 12 Months from 03-Nov-2024 to 02-Nov-2025

Auto Renewal

On

Automatically Renewal For 12 Months On 03-Nov-2025

Requested Start Date 03 Nov 2024

Enter a date between 31-Oct-2024 & 28-Jan-2025

Billing Frequency

Monthly Billing

Prepaid Term

Annual Billing

Quarterly Billing

Usage Based Billing

Co-Term to an End Date

Summary

Messages

Configuration Summary

Hide 20 items


Sort: Category

PRODUCTS	QUANTITY	EXTENDED LIST PRICE
HARDWARE		
CW9176-RTG	10	
SOFTWARE		
CISCO-NETWORK-SUB	1	0.00
LC-CW-E	5	---
LC-CW-E	10	---
LC-SPACES-E	5	---
LC-SPACES-E	10	---

© 2025 Cisco and/or its affiliates. All rights reserved.

Page 21 of 46

Step 13: Review order details



Cisco DNA software for wireless product overview

Cisco DNA software subscriptions deliver an unbound network on an open and extensible architecture to help you navigate the digital journey. Benefits include lower initial costs, investment protection, agility to respond more quickly to business needs, and better budget predictability. These 3-, 5-, and 7-year subscriptions include full Cisco capabilities supported by Cisco Software-Defined Access (SD-Access), AI / ML, analytics, automation, and security. For a full list of Cisco DNA software features, please visit the [Wireless Feature Matrix](#).

More details about the available features in each tier can be found at <https://www.cisco.com/go/dnawireless>.

Cisco platforms supported by Cisco DNA wireless subscriptions

The following access point platforms are supported:

- All Cisco Catalyst 9100 Access Points are fully supported, except Wi-Fi 7 APs. The following Wireless LAN Controller (WLC) platforms are supported:
- [Cisco Catalyst 9800 Series Wireless Controllers](#).

How to order a Cisco DNA wireless subscription

Cisco DNA software subscriptions for wireless can be ordered through the following methods:

- Cisco DNA software subscription, along with an access point order
- Standalone Cisco DNA software subscription

Ordering Cisco DNA subscriptions along with an access point order

- Cisco DNA software subscriptions are available to order along with all Cisco access points.
- For convenience, Cisco DNA Advantage 5-year is preselected as the default option with Cisco Catalyst 9100 Access Points.

To order a Cisco DNA subscription with access points in Cisco Commerce, follow these steps:

1. Enter the access point SKU. For example, CW9166I-B.
2. Select the appropriate AIR-DNA (AIR-DNA-A or AIR-DNA-E) license type.
3. Choose the Cisco DNA license term (3, 5, or 7 years).

+

1.0

AIR-DNA

more

CISCO DNA for Wireless - CHOOSE ONLY QTY 1 HERE

Success Track: CAMPUS NETWORK

Invalid as of 07-Jul-2023 08:54:51 PDT

Edit Options

Edit Service/Subscription

Validate

Recommended Content

Add Note

More Actions

Add Subtotal

3 days0.0010.000.000.00

Figure 3. Specifying AIR-DNA

Configuration SummaryView Full Summary

Category	Qty	Extended List Price (USD)
DNAC On-Prem Subscription		
AIR-DNA-A	1	0.00
AIR-DNA-A-5Y 60 Mth(s)		1,094.17
PI-LFAS-AP-T	1	0.00
PI-LFAS-AP-T-5Y 60 Mth(s)		0.00
AIR-DNA-A-T	1	0.00
AIR-DNA-A-T-5Y 60 Mth(s)		0.00
AIR-DNA-NWSTACK-A	1	0.00
SPACES-EXT-T	1	0.00
SPACES-EXT-5Y 60 Mth(s)		0.00
Total		1,094.17
Estimated Lead Time	28 days	
Reset Configuration CancelDone		

Option SearchMultiple Options Search

AIR-DNA > DNAC On-Prem Subscription

DNAC On-Prem Subscription

SKU	Qty	Estimated Lead Time	Unit List Price (USD)
AIR-DNA-A Wireless Cisco DNA On-Prem Advantage, Term Lic More	1	3 days	0.00
AIR-DNA-E Wireless Cisco DNA On-Prem Essential, Term Lic More	Qty	3 days	0.00

Clear SelectionShow Incompatible SKUs

Figure 4. Choosing a license type

Configuration SummaryView Full Summary

Category	Qty	Extended List Price (USD)
DNAC On-Prem Subscription		
AIR-DNA-A	1	0.00
AIR-DNA-A-5Y 60 Mth(s)		1,094.17
PI-LFAS-AP-T	1	0.00
PI-LFAS-AP-T-5Y 60 Mth(s)		0.00
AIR-DNA-A-T	1	0.00
AIR-DNA-A-T-5Y 60 Mth(s)		0.00
AIR-DNA-NWSTACK-A	1	0.00
SPACES-EXT-T	1	0.00
SPACES-EXT-5Y 60 Mth(s)		0.00
Total		1,094.17
Estimated Lead Time	28 days	
Reset Configuration CancelDone		

Option SearchMultiple Options Search

AIR-DNA > DNAC On-Prem Subscription > DNAC On-Prem Subscription > AIR-DNA-A

Cisco SpacesSubscription

SKU	Qty	Estimated Lead Time	Unit List Price (USD)
SPACES-EXT-T Cisco Spaces Extend Term License for Cisco DNA Advantage Software Subscriptions Duration Month(s) SPACES-EXT-3Y Range 36 to 59 36 0.00 SPACES-EXT-5Y Range 60 to 83 Requested Start/End Date 60 0.00 SPACES-EXT-7Y Range 84 to 84 84 0.00			

Figure 5. Choosing a license term

© 2025 Cisco and/or its affiliates. All rights reserved.

Page 24 of 46

Cisco Catalyst 9800 Series highlights

Built from the ground up for intent-based networking and Cisco DNA, the Cisco Catalyst 9800 Series Wireless Controllers bring together the magic of Cisco IOS XE and Cisco RF excellence, to create a best-in-class wireless experience for your evolving and growing organization. The 9800 Series wireless controllers are built on an open and programmable architecture with built-in security, streaming telemetry, and rich analytics.

The Cisco Catalyst 9800 Series Wireless Controllers are feature rich and enterprise ready to power your business-critical operations and transform end-customer experiences:

- High availability and seamless software updates, enabled by hot patching, keep your clients and services always on during planned and unplanned events.
- Secure the air, devices, and users with the 9800 Series controllers. Wireless infrastructure becomes the strongest first line of defense with Cisco Encrypted Traffic Analytics (ETA) and SD-Access. The controllers come with built-in security features such as secure boot, runtime defenses, image signing, integrity verification, and hardware authenticity.
- Deploy anywhere to enable wireless connectivity everywhere. Whether on-premises, in a public or private cloud, or embedded on a switch or access point, the Cisco Catalyst 9800 Series has multiple deployment and scale options to best meet your organization's needs.
- Built on a modular operating system, the 9800 Series' open and programmable APIs enable automation of your day-0 to day-N network operations. Model-driven streaming telemetry provides deep insights into the health of your network and clients.

Cisco Catalyst 9800 Series Wireless Controllers are available in multiple form factors to best suit your deployment preference:

- Cisco Catalyst 9800 Series Wireless Controller appliances (CW9800M, CW9800H1, CW9800H2, C9800-L, C9800-40, and C9800-80)
- Cisco Catalyst 9800 Wireless Controllers for Cloud
<https://www.cisco.com/c/dam/en/us/products/collateral/wireless/catalyst-9800-series-wireless-controllers/nb-06-cat9800-ser-aag-ctp-en.pdf>.

Wireless platform support summary and part numbers

Table 25. Wireless platform support summary

Product family	Product name	Description
Cisco Catalyst 9800 Series Wireless Controller appliances	Cisco Catalyst CW9800M	Powerful and efficient 1RU design for medium sized deployments. Supports up to 3000 APs and 32000 clients with up to 50 Gbps.
	Cisco Catalyst CW9800H1	Powerful and efficient 1RU design for large sized deployments with 4 x 25 Gbps and 8 x 1/10 Gbps uplinks. Supports up to 6000 APs and 64000 clients with up to 100 Gbps.
	Cisco Catalyst CW9800H2	Powerful and efficient 1RU design with 2 x 40 Gbps and 8 x 1/10 Gbps uplinks. Supports up to 6000 APs and 64000 clients with up to 100 Gbps.
	Cisco Catalyst 9800-L Wireless Controller	9800-L: Perfect for small organizations, this controller offers seamless software updates
	Cisco Catalyst 9800-40 Wireless Controller	9800-40: Fixed wireless controller with seamless software updates
	Cisco Catalyst 9800-80 Wireless Controller	9800-80: Modular wireless controller with 100G modular uplink and seamless software updates
Cisco Catalyst 9800 Wireless Controllers for Cloud	Cisco Catalyst 9800-CL Wireless Controller for Cloud (Private cloud: VMware ESXI, KVM, Cisco NFVIS on ENCS) (Public cloud: AWS Marketplace)	Wireless controller that can be deployed in a private cloud or in a public cloud as Infrastructure as a Service (IaaS)
Cisco Catalyst 9800 SD-Access Embedded Wireless	Cisco Catalyst 9800 Embedded Wireless for Switch	Cisco Catalyst 9800 software sub-package for Cisco Catalyst 9000 switching platform

Table 26. Wireless platform part numbers

Product family	Part numbers	Description
Cisco Catalyst CW9800M Wireless Controller	PWR-CH1-750WACR	Cisco 750W AC Power Supply
	A1K-1RU-REAR=	Rear rack mount kit for CW9800
Cisco Catalyst CW9800H1 Wireless Controller	PWR-CH1-750WACR	Cisco 750W AC Power Supply
	PWR-CH1-950WDCR	Cisco 950W DC Power Supply
	A1K-1RU-REAR=	Rear rack mount kit for CW9800
Cisco Catalyst CW9800H2 Wireless Controller	PWR-CH1-750WACR	Cisco 750W AC Power Supply
	PWR-CH1-950WDCR	Cisco 950W DC Power Supply
	A1K-1RU-REAR=	Rear rack mount kit for CW9800
Cisco Catalyst 9800-L Wireless Controller	C9800-L-C-K9	Cisco Catalyst 9800-L-C Wireless Controller_Copper Uplink
	C9800-L-F-K9	Cisco Catalyst 9800-L-F Wireless Controller_Fiber Uplink
	C9800-AC-110W	Cisco Catalyst 9800-L Wireless Controller Power Adapter
	C9800-AC-110W=	Cisco Catalyst Wireless Controller 110W AC Power Adapter Spare
	LIC-C9800-DTLS-K9	Cisco Catalyst 9800 Wireless Controller DTLS license
	C9800L-RMNT	C9800 Wireless Controller Rack Mount Tray
	C9800L-RMNT=	Spare C9800 Wireless Controller Rack Mount Tray
	C4948E-BKT-KIT=	C49xxE front and rear mount brackets
Cisco Catalyst 9800-40 Wireless Controller	C9800-40-K9	Cisco Catalyst 9800-40 Wireless Controller
	C9800-AC-750W-R	Cisco Catalyst 9800-40 750W AC Power Adapter Reverse Air (part of the system configuration)
	C9800-AC-750W-R=	Cisco Catalyst 9800-40 750W AC Power Adapter Reverse Air (spare)
	LIC-C9800-DTLS-K9	Cisco 9800 Wireless Controller DTLS license

Product family	Part numbers	Description
Cisco Catalyst 9800-80 Wireless Controller	C9800-80-K9	Cisco Catalyst 9800-80 Wireless Controller
	C9800-AC-1100W	Cisco Catalyst Wireless Controller 1100W AC Power Adapter (part of the system configuration)
	C9800-AC-1100W=	Cisco Catalyst Wireless Controller 1100W AC Power Adapter (spare)
	C9800-DC-950W	Cisco Catalyst Wireless Controller 950W DC Power Adapter (part of the system configuration)
	C9800-DC-950W=	Cisco Catalyst Wireless Controller 950W DC Power Adapter (spare)
	LIC-C9800-DTLS-K9	Cisco Catalyst 9800 Wireless Controller DTLS license
Cisco Catalyst 9800-CL Wireless Controller for Cloud	L-C9800-CL-K9	Cisco Catalyst 9800-CL Wireless Controller
Modules for 9800-80	C9800-18X1GE (=)	Cisco Catalyst 9800-80 GE module
	C9800-10X10GE (=)	Cisco Catalyst 9800-80 10 GE module
	C9800-1X40GE (=)	Cisco Catalyst 9800-80 1-port 40 GE module
	C9800-2X40GE (=)	Cisco Catalyst 9800-80 2-port 40 GE module
	C9800-1X100GE (=)	Cisco Catalyst 9800-80 1-port 100 GE module

Cisco Catalyst 9800 Series Wireless Controller ordering steps

Cisco Catalyst 9800 Series Wireless Controllers can be ordered from [Cisco Commerce](#).

CW9800M ordering steps

Table 27. Ordering steps for Cisco Catalyst CW9800M

1. Type “CW9800M,” then add “CW9800M”and select “Edit Options.”	
Part number	Description
CW9800M	Cisco Catalyst CW9800M Wireless Controller (ships with one AC power adapter)

Table 28. Software Image

2. The software image is auto selected.	
Part number	Description
SW-9800M-1714	Software image (current version of software installed at factory)

Table 29. Power adaptor selection

3. The power adapter is auto selected.	
Part number	Description
PWR-CH1-750WACR	Cisco 750W AC power adapter

Table 30. Country specific power cable

4. Choose the country-specific power cable (presented after selecting the power adapter).			
Part number	Description	Part number	Description
CAB-ACC	China AC Type A Power Cable	CAB-IND	India AC Type A Power Cable
CAB-ACR	Argentina AC Type A Power Cable	CAB-L620P-C13-JPN	Japan AC Type A Power Cable
CAB-ACU	UK AC Type A Power Cable	CAB-AC	North America AC Type A Power Cable
CAB-C13-C14-2M	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors	CAB-ACA	Australia AC Type A Power Cable
CAB-C13-C14-AC	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors	CAB-L620P-C13-US	US Standard Power Cable
CAB-C13-C14-JMPRCAB-ACS	Cisco Power Cable	CAB-JPN	Japan AC Type A Power Cable
CAB-ACI	Italy AC Type A Power Cable	CAB-C13-CBN	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors
CAB-C15-ACB	Brazil AC Type A Power Cable	CAB-ACE	Continental Europe AC Type A Power Cable
CAB-ACS	Switzerland AC Type A Power Cable		

CW9800H1/CW9800H2 ordering steps

Table 31. Ordering steps for Cisco Catalyst CW9800H1/H2

1. Type “CW9800H1 or CW9800H2,” then add “CW9800H1 or CW9800H2” and select “Edit Options.”	
Part number	Description
CW9800H1 or CW9800H2	Cisco Catalyst CW9800H1 or CW9800H2 Wireless Controller

Table 32. Software image

2. Click “Software,” and SC980040K9-1610 is auto selected.	
Part number	Description
SW9800H-1714	Software image (current version of software installed at factory)

Table 33. Power adapter selection

3. Click “Power” and choose from the options below.	
Part number	Description
PWR-CH1-750WACR	Cisco 750W AC power adapter
PWR-CH1-950WDCR	Cisco 950W DC power adapter

Table 34. Country specific power cable

4. Select the presented power cable type from the list below after clicking the AC power adapter.			
Part number	Description	Part number	Description
CAB-ACC	China AC Type A Power Cable	CAB-IND	India AC Type A Power Cable
CAB-ACR	Argentina AC Type A Power Cable	CAB-L620P-C13-JPN	Japan AC Type A Power Cable
CAB-ACU	UK AC Type A Power Cable	CAB-AC	North America AC Type A Power Cable
CAB-C13-C14-2M	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors	CAB-ACA	Australia AC Type A Power Cable
CAB-C13-C14-AC	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors	CAB-L620P-C13-US	US Standard Power Cable
CAB-C13-C14-JMPR	Cisco Power Cable	CAB-JPN	Japan AC Type A Power Cable

4. Select the presented power cable type from the list below after clicking the AC power adapter.

Part number	Description	Part number	Description
CAB-ACI	Italy AC Type A Power Cable	CAB-C13-CBN	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors
CAB-C15-ACB	Brazil AC Type A Power Cable	CAB-ACE	Continental Europe AC Type A Power Cable
CAB-ACS	Switzerland AC Type A Power Cable		

Note: No cable option is presented when the DC power adapter is selected.

C9800-L-F-K9 and C9800-L-C-K9 ordering steps

Table 35. Ordering steps for Cisco Catalyst 9800-L Wireless Controllers

1. Type “C9800-L-C-K9/ C9800-L-F-K9,” then add “C9800-L-C-K9/ C9800-L-F-K9”and select “Edit Options.”

Part number	Description
C9800-L-C-K9	Cisco Catalyst 9800-L-C Wireless Controller_Copper Uplink (ships with one AC power adapter)
C9800-L-F-K9	Cisco Catalyst 9800-L-F Wireless Controller_Fiber Uplink (ships with one AC power adapter)

Table 36. Optional Data Encryption License

2. Click “Data Encryption” and select DTLS license if encryption of client data is required (optional).

Part number	Description
LIC-C9800-DTLS-K9	Cisco Catalyst 9800 Wireless Controller DTLS license

Table 37. Software image

3. The software image is auto selected.

Part number	Description
SC9800LK9-xxxx	Software image (xxxx = current version of software installed at factory)

Table 38. Power adapter selection

4. The power adapter is auto selected.

Part number	Description
C9800-AC-110W	Cisco Catalyst 9800-L 110W AC power adapter

Table 39. Country-specific power cable

5. Choose the country-specific power cable (presented after selecting the power adapter).			
Part number	Description	Part number	Description
CAB-AC-C5	AC Power Cord, Type C5, US, Canada	CAB-AC-C5-ITA	AC Power Cord, Type C5, Italy
CAB-AC-C5-ARG	AC Power Cord, Type C5, Argentina	CAB-AC-C5-JAP	AC Power Cord, Type C5, Japan
CAB-AC-C5-AUS	AC Power Cord, Type C5, Australia	CAB-AC-C5-KOR	AC Power Cord, Type C5, Korea
CAB-AC-C5-BR	AC Power Cord, Type C5, Brazil	CAB-AC-C5-SAF	AC Power Cord, Type C5, South Africa
CAB-AC-C5-BRA	AC Power Cord, Type C5, Brazil	CAB-AC-C5-SWI	AC Power Cord, Type C5, Switzerland
CAB-AC-C5-CHI	AC Power Cord, Type C5, China	CAB-AC-C5-TWN	AC Power Cord, Type C5, Taiwan
CAB-AC-C5-EUR	AC Power Cord, Type C5, Europe	CAB-AC-C5-UK	AC Power Cord, Type C5, UK
CAB-AC-C5-IND	AC Power Cord, Type C5, India	CAB-AC-C5-ITA	AC Power Cord, Type C5, Italy
CAB-AC-C5	AC Power Cord, Type C5, US, Canada		

C9800-40-K9 ordering steps**Table 40.** Ordering steps for Cisco Catalyst 9800-40

1. Type “C9800-40-K9,” then add “C9800-40-K9”and select “Edit Options.”	
Part number	Description
C9800-40-K9	Cisco Catalyst 9800-40 Wireless Controller (ships with one AC power adapter)

Table 41. Optional Data Encryption license

2. Click “Data Encryption” and select DTLS license if encryption of client data is required (optional).	
Part number	Description
LIC-C9800-DTLS-K9	Cisco Catalyst 9800 Wireless Controller DTLS license

Table 42. Software Image

3. The software image is auto selected.	
Part number	Description
SC980040K9-xxxx	Software image (xxxx = current version of software installed at factory)

Table 43. Power adapter selection

4. The power adapter is auto selected.	
Part number	Description
C9800-AC-750W-R	Cisco Catalyst 9800-40 750W AC power adapter

Table 44. Country-specific power cable

5. Choose the country-specific power cable (presented after selecting the power adapter).			
Part number	Description	Part number	Description
CAB-ACC	China AC Type A Power Cable	CAB-IND	India AC Type A Power Cable
CAB-ACR	Argentina AC Type A Power Cable	CAB-L620P-C13-JPN	Japan AC Type A Power Cable
CAB-ACU	UK AC Type A Power Cable	CAB-AC	North America AC Type A Power Cable
CAB-C13-C14-2M	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors	CAB-ACA	Australia AC Type A Power Cable
CAB-C13-C14-AC	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors	CAB-L620P-C13-US	US Standard Power Cable
CAB-C13-C14-JMPRCAB-ACS	Cisco Power Cable	CAB-JPN	Japan AC Type A Power Cable
CAB-ACI	Italy AC Type A Power Cable	CAB-C13-CBN	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors
CAB-C15-ACB	Brazil AC Type A Power Cable	CAB-ACE	Continental Europe AC Type A Power Cable
CAB-ACS	Switzerland AC Type A Power Cable		

C9800-80-K9 ordering steps**Table 45.** Ordering steps for Cisco Catalyst 9800-80

1. Type "C9800-80-K9," then add "C9800-80-K9"and select "Edit Options."	
Part number	Description
C9800-80-K9	Cisco Catalyst 9800-80 Wireless Controller

Table 46. Optional Data Encryption License

2. Click “Data Encryption” and select DTLS license if encryption of client data is required (optional).	
Part number	Description
LIC-C9800-DTLS-K9	Cisco Catalyst 9800 Wireless Controller DTLS license

Table 47. Software image

3. Click “Software,” and SC980040K9-1610 is auto selected.	
Part number	Description
SC980080K9-xxxx	Software image (xxxx = current version of software installed at factory)

Table 48. Power adaptor selection

4. Click “Power” and choose from the options below.	
Part number	Description
C9800-AC-1100W	Cisco Catalyst Wireless Controller 1100W AC power adapter
C9800-DC-950W	Cisco Catalyst Wireless Controller 950W DC power adapter

Table 49. Country specific power cable

5. Select the presented power cable type from the list below after clicking the AC power adapter.			
Part number	Description	Part number	Description
CAB-ACC	China AC Type A Power Cable	CAB-IND	India AC Type A Power Cable
CAB-ACR	Argentina AC Type A Power Cable	CAB-L620P-C13-JPN	Japan AC Type A Power Cable
CAB-ACU	UK AC Type A Power Cable	CAB-AC	North America AC Type A Power Cable
CAB-C13-C14-2M	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors	CAB-ACA	Australia AC Type A Power Cable
CAB-C13-C14-AC	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors	CAB-L620P-C13-US	US Standard Power Cable
CAB-C13-C14-JMPR	Cisco Power Cable	CAB-JPN	Japan AC Type A Power Cable
CAB-ACI	Italy AC Type A Power Cable	CAB-C13-CBN	Cabinet Jumper Power Cord, 250 VAC 10 A, C13-C14 Connectors

5. Select the presented power cable type from the list below after clicking the AC power adapter.

Part number	Description	Part number	Description
CAB-C15-ACB	Brazil AC Type A Power Cable	CAB-ACE	Continental Europe AC Type A Power Cable
CAB-ACS	Switzerland AC Type A Power Cable		

Note: No cable option is presented when the DC power adapter is selected.

Table 50. Uplink module selection

6. Click “Modules” and select one of the following uplink modules.

Part number	Description
C9800-10X10GE	Cisco Catalyst 9800-80 10 GE Module
C9800-2X40GE	Cisco Catalyst 9800-80 2 Port 40 GE Module

Note: If none of the uplink modules is chosen, C9800-BLANK module will automatically be added to the configuration.

Cisco Catalyst 9800-CL Wireless Controller for Cloud ordering steps

Table 51. Ordering steps for Cisco Catalyst 9800-CL

1. Type “C9800-CL-K9,” then add “C9800-CL-K9” and select “Edit Options.”

Part number	Description
C9800-CL-K9	Cisco Catalyst 9800 Wireless Controller for Cloud

Table 52. Optional Data Encryption License

2. Click “Data Encryption” and select DTLS license if encryption of client data is required (optional).

Part number	Description
LIC-C9800-DTLS-K9	Cisco Catalyst 9800-CL Wireless Controller DTLS license

Table 53. Software image

3. Click “Software” and choose one of the following software images.	
Part number	Description
SC9800CLTARK9-xxxx	Cisco Catalyst 9800-CL Wireless Controller – ENFV
SC9800CLOVAK9-xxxx	Cisco Catalyst 9800-CL Wireless Controller – VMware ESXi
SC9800CLQCOK9-xxxx	Cisco Catalyst 9800-CL Wireless Controller – KVM
SC9800CLAMIK9-xxxx	Cisco Catalyst 9800-CL Wireless Controller – AWS

(xxxx = current version of software installed at factory)

After submission you will get an eDelivery Order Notification email.

1. After placing your order on CCW, do one of the following, based on your software selection in step 3.
 - Private cloud
 - Go to software.cisco.com.
 - Download the appropriate image as selected in CCW.
 - Public cloud
 - Go to AWS Marketplace, and search for “C9800-CL.”
 - Continue to subscribe and instantiate the C9800 wireless controller for AWS.

Catalyst 9800 SD-Access embedded wireless ordering steps

1. Prerequisite: Customer has or will buy a Cisco Catalyst 9300, 9400 or 9500 Series Switch and the required Cisco DNA Advantage or Cisco DNA Essentials licenses.
 2. Prerequisite: Customer has or will buy Cisco access points with a Cisco DNA Advantage or Cisco DNA licenses for each access point.
 1. Navigate to the Cisco Catalyst 9300, 9400 or 9500 downloads section on software.cisco.com.
 2. Download the “C9800-SW” sub-package.
 3. Install the sub-package on the Cisco Catalyst 9300, 9400 or 9500 Series Switch.
- * **Note:** AIR-DNA Advantage with a 5-year subscription option is selected by default.

Table 54. Antennas

Antenna part number	Description
C-ANT9101=	2.4/5/6 GHz Ceiling mount omni antenna, 8-port, DART, Self ID
C-ANT9102=	2.4/5/6 GHz Multi mount omni antenna, 8-port, DART, Self ID
C-ANT9103=	2.4/5/6 GHz Directional antenna, 8-port, DART, Self ID
AIR-AP-BRACKET-9=	C9130AXE antenna bracket
AIR-ANT2524DW-R	Cisco Aironet dual-band dipole antenna; White; Peak Gain 2 dBi at 2.4. GHz and 4 dBi at 5 GHz
AIR-ANT2535SDW-R	Cisco Aironet short dual-band omni antenna, Peak Gain 3 dBi at 2.4. GHz and 5 dBi at 5 GHz
AIR-ANT2524DG-R	Cisco Aironet dual-band dipole antenna; Grey; Peak Gain 2 dBi at 2.4. GHz and 4 dBi at 5 GHz
AIR-ANT2524DB-R	Cisco Aironet dual-band dipole antenna; Black; Peak Gain 2 dBi at 2.4. GHz and 4 dBi at 5 GHz
AIR-ANT2524DW-RS	Cisco Aironet dual-band dipole antenna; White; Peak Gain 2 dBi at 2.4. GHz and 4 dBi at 5 GHz
AIR-ANT2535SDW-RS	Cisco Aironet short dual-band omni antenna, Peak Gain 3 dBi at 2.4. GHz and 5 dBi at 5 GHz
AIR-ANT2524V4C-RS=	Cisco Aironet omni antenna, ceiling mount, Peak Gain 2 dBi at 2.4. GHz and 4 dBi at 5 GHz
AIR-ANT2544V4M-RS=	Cisco Aironet omni antenna, wall/pole mount, Peak Gain 2 dBi at 2.4 GHz and 4 dBi at 5 GHz
AIR-ANT2566P4W-RS=	Cisco Aironet patch antenna, wall/pole mount, Peak Gain 6 dBi at 2.4 GHz and 6 dBi at 5 GHz
AIR-ANT2566D4M-RS=	Cisco Aironet directional antenna, wall/pole mount, Peak Gain 6 dBi at 2.4 GHz and 6 dBi at 5 GHz
AIR-ANT2513P4M-NS=	Cisco Aironet directional antenna, wall/pole mount, Peak Gain 13 dBi at 2.4 GHz and 13 dBi at 5 GHz
AIR-ANT2566P4W-DS=	Cisco Aironet patch antenna, wall/pole mount, Peak Gain 6 dBi at 2.4 GHz and 6 dBi at 5 GHz, 4-port DART connector
AIR-ANT2566D4M-DS=	Cisco Aironet directional antenna, wall/pole mount, Peak Gain 6 dBi at 2.4 GHz and 6 dBi at 5 GHz, 4-port DART connector

Select 2.4- and 5-GHz dual-band external configurable or spare antennas (applicable if C9124AXE access point is selected).

Table 55. Antenna type selection

Part number	Generation	Qty	Description
AIR-ANT2568VG-NS	SIA	4	2.4GHz 6dBi / 5GHz 8dBi Omnidirectional Antenna, Connectors N-Male
AIR-ANT2547VG-NS	SIA	4	2.4GHz 4dBi / 5GHz 7dBi Omnidirectional Colinear Array Antenna, Connectors N-Male
AIR-ANT2568VG-NS=	SIA	4	2.4GHz 6dBi / 5GHz 8dBi Omnidirectional Antenna, Connectors N-Male
AIR-ANT2547VG-NS=	SIA	4	2.4GHz 4dBi / 5GHz 7dBi Omnidirectional Colinear Array Antenna, Connectors N-Male
AIR-ANT2588P4M-NS=	SIA	1	2.4GHz 8dBi / 5GHz 8dBi 4-Element Dual-Polarized Patch Antenna, Connectors N-Female Bulkhead (4x RF Coaxial Cable needed)
AIR-ANT2513P4M-NS=	SIA	1	2.4GHz 13dBi / 5GHz 13dBi Dual-Band Polarization Diverse Patch Array Antenna, Connectors N-Female Bulkhead (4x RF Coaxial Cable needed)
AIR-ANT2547V-N=	Legacy	4	2.4GHz 4dBi / 5GHz 7dBi Omnidirectional Colinear Array Antenna, Connectors N-Male
AIR-ANT2547VG-N=	Legacy	4	2.4GHz 4dBi / 5GHz 7dBi Omnidirectional Colinear Array Antenna, Connectors N-Male (Grey Color)
AIR-ANT2588P3M-N=	Legacy	1	2.4GHz 8dBi / 5GHz 8dBi 3-Element Dual-Polarized Patch Antenna, Connectors N-Female Bulkhead(3x RF Cable Coaxial needed)
AIR-ANT2450V-N=	Legacy	4	2.4GHz 5dBi Omnidirectional Colinear Array Antenna, Connectors N-Male
AIR-ANT2480V-N=	Legacy	4	2.4GHz 8dBi Omnidirectional Colinear Array Antenna, Connectors N-Male
AIR-ANT5180V-N=	Legacy	4	5GHz 8dBi 2-Element Omnidirectional Colinear Array Antenna, Connectors N-Male
AIR-ANT2513P4M-N=	Legacy	1	2.4GHz 13dBi / 5GHz 13dBi Dual-Band Polarization Diverse Patch Array Antenna, Connectors N-Female Bulkhead (4x RF Coaxial Cable needed)

RF cables and lightning arrestor (applicable if the C9124 access point is selected, to be ordered separately, as per the requirement)

Table 56. RF Cable and lightning arrestor options

Part number	Description
AIR-CAB005LL-N=	RF Cable, 5 ft Low-loss, N Connectors
AIR-CAB010LL-N=	RF Cable, 10 ft Low-loss, N Connectors
AIR-ACC245LA-N	Lightning Arrestor (If C9124AXE is connected to remote antenna through cable)

Select access point mounting brackets (applicable if the C9130 or C9120 or C9115 or C9105 access point is selected).

Table 57. Bracket options

Part number	Description
AIR-AP-NO-BRACKET	Select this option if no bracket is required
AIR-AP-BRACKET-1	Low-profile access point mounting bracket, default option
AIR-AP-BRACKET-2	Universal bracket for access point mounting
AIR-AP-BRACKET-W4	Bracket for 9105w access point wall mounting
AIR-AP-BRACKET-8	Bracket for 9105i access point mounting

Select access point mounting brackets. (applicable if the C9124 access point is selected).

Table 58. Bracket options

Part number	Description
AIR-AP-NO-BRACKET	Select this option if no bracket is required
AIR-MNT-VERT1	Vertical mounting bracket for Cisco Catalyst 9124AXD/AXE access point, will be option in CCW
AIR-MNT-VERT1=	Vertical mounting bracket for Cisco Catalyst 9124AXD/AXE access point
AIR-MNT-ART1=	Articulating mounting bracket for Cisco Catalyst 9124AXD access point
AIR-MNT-HORZ1=	Horizontal mounting bracket for Cisco Catalyst 9124AXI/AXD access point
AIR-MNT-VERT2=	Vertical mounting bracket for Cisco Catalyst 9124AXD/AXE access point with AC/DC PSU
AIR-MNT-STRAND1=	Strand mounting bracket for Cisco Catalyst 9124AXI/AXD access point

Select ceiling grid clips (applicable if the C9130 or C9120 or C9115 or C9105 access point is selected).

Table 59. Ceiling clip options

Part number	Description
AIR-AP-T-RAIL-R	Ceiling grid clip (recessed mounting); this is the default option
AIR-AP-T-RAIL-F	Ceiling grid clip (flush mounting)
AIR-CHNL-ADAPTER	Optional adapter for channel-rail ceiling grid profile

Select the access point powering options (applicable if the C9130 or C9120 or C9115 or C9105 access point is selected, to be ordered separately, as per the requirement).

Table 60. Power options

Source	Description
CW-INJ-8	802.3bt, 60W, Cisco Power Injector, 10 Gbps Ethernet
AIR-PWRINJ6=	802.3at Cisco Power Injector 802.3af
AIR-PWRINJ5=	Cisco Power Injector
PoE+ via switch port	Any 802.3at (30.0 W) compliant switch port

Select the access point powering options (applicable if the C9124 access point is selected, to be ordered separately, as per the requirement).

The Catalyst 9124AX Series Access Points can be powered by multiple sources: AC, DC, or Power over Ethernet (PoE). For AC powering, an external AC-to-DC power adapter is required. For DC powering, a 2-pin DC connector is included with every access point. The access point can also be powered by Cisco Universal Power over Ethernet (Cisco UPOE) or PoE+ (802.3at) directly from a switch or power injector.

Table 61. Power source

Part number	Description	Use case
AIR-PWRINJ-60RGD1=	Power injector, 60W, outdoor, North America plug	Outdoor-rated 60W power injector with North American AC plug
AIR-PWRINJ-60RGD2=	Power injector, 60W, outdoor, un-connectorized	Outdoor-rated 60W power injector, unterminated AC cable for international use
AIR-PWRINJ-60-PMK=	Pole mount kit for AIR-PWRINJ-60	Required for pole mounting for AIR-PWRINJ-60RGD1= or AIR-PWRINJ-60RGD2=
AIR-PWRINJ6=	Power injector, 802.3at, indoor	Indoor-rated, 802.3at-compliant power injector

Note: Please check access point data sheets for power requirements. If AIR-PWRINJ5 is used, the access point will work with reduced features. For more details, refer to the respective access point data sheet.

Catalyst 9124AX Series outdoor access points support fiber backhaul.

The SFP port is built into the access point, but the mechanical interface is external to the access point.

A special SFP adapter/gland kit is needed to interface the fiber cable to the access point.

Table 62. Adapter options

Adaptor Part number	Description	Use case
AIR-ACC-KIT1=	Accessory kit for Catalyst 9124AX	Contains 5x SFP glands
GLC-LX-SM-RGD	1000BASE-LX single-mode rugged SFP	Long-distance fiber backhaul on single-mode fiber
GLC-SX-MM-RGD	1000BASE-SX multi-mode rugged SFP	Shorter-distance fiber backhaul on multimode fiber
GLC-T-RGD	1000BASE-T SFP, industrial temp	GE electrical interface for bridging wired clients such as video cameras or switches

Accessories (applicable if the C9124 access point is selected, to be ordered separately, as per the requirement).

Table 63. Accessory options

Accessories part number	Description
AIR-ACC-KIT1=	Accessory kit for Catalyst 9124AX (5x ethernet, 2 dust cap, ground lug, DC plug kit)
C9124-CVR1=	Paintable cover for Catalyst 9124AX
AIR-SFP-KIT1=	SFP installation kit for Catalyst 9124AX
AIR-ACC-PS-MNT1=	AC/DC adapter mount bracket for AIR-MNT-HORZ1=

Default accessories shipped with the box

C9800-L accessories kit

74-1151990-XX	TPASY WIRELESS MECHANICAL ACCESSORY KIT
78-101471-XX	CDOC; PNTR CARD C9800-L

C9800-40 accessories kit

69-1937-01_C0	MECHKIT, MOUNTING BRACKETS,1RU
47-20184-01_A0	LBL, EPUP, 10YR, China RoHS
72-4334-02_B0	CABLE, ROUND, RJ45 TO D9 FEMALE,3000mm,FTP,SERIAL
79-0087-01_A0	STRAP, DISPOSABLE ESD WRIST, CLIP TERMINATION
69-2016-01_A0	MECHKIT, CABLE RETAINER, 1RU, JACKPOT, MCP
78-21649-xx	CDOC; PNTR_CARD
502-00275-01_A0	PKG, BAG,10"X15",2MIL, PE, NC

C9800-80 accessories kit

32-0629-01 (Qty:2pcs)	LUG TWO HOLE#6AWG#10 STUD BLUE
48-0700-01 (Qty:4pcs)	SCR, M, THS, PH10-32X038" L, ZNwPCH
72-4334-02_B0	CABLE, ROUND, RJ45 TO D9 FEMALE, 3000mm, FTP, SERIAL
78-21649-xx	CDOC; PNTR_CARD
79-0087-01_A0	STRAP, DISPOSABLE ESD WRIST, CLIP TERMINATION
502-00275-01_A0	PKG, BAG,10"X15",2MIL, PE, NC

Licensing

The Cisco Catalyst 9800 Series Wireless Controllers require Unified Licensing or Smart Licensing.

No licenses are required to boot up a **Cisco Catalyst 9800 Series Wireless Controller**. However, each access point that connects to the wireless controller requires a license to be entitled to connect and for full radio functionality.

Two kinds of licensing are available:

- Cisco Wireless unified licenses are available with Cisco Networking Subscriptions. Unified licenses are required for Wi-Fi 7 APs. Unified licensing entitles the user to both cloud and on-premises management of their APs.
- Cisco Smart Licensing is a term-based licensing model available for 6E and earlier APs.
- To deploy unified licensing or Smart Licensing on a WLC, you must first set up a Smart Account on Cisco Software Central (software.cisco.com).

For more detailed overview on Cisco Licensing, go to cisco.com/go/licensingguide.

- SLR mode
 - Specific License Reservation (SLR) is a feature used in highly secure networks. It provides a method for customers to deploy a software license on a device (product instance) without communicating usage information to Cisco. There will be no communication with Cisco or a satellite. A license is reserved for every controller. It is node-based licensing.

Multiple levels of license are supported on the **Cisco Catalyst 9800 Series Wireless Controllers**. The controllers can be configured to function at any one of these levels.

- **Cisco Wireless or Cisco DNA Essentials:**
At this level the Cisco DNA Essentials feature set will be supported. The former Network Essentials (NE) feature set is included within this feature tier.
- **Cisco Wireless or Cisco DNA Advantage:**
At this level the Cisco DNA Advantage feature set will be supported. The former Network Advantage (NA) feature set is included within this feature tier.

For customers who purchase Cisco Wireless or Cisco DNA Essentials, Network Essentials will be supported and will continue to function even after term expiration. And for customers who purchase Cisco Wireless or Cisco DNA Advantage, Network Advantage will be supported and will continue to function even after term expiration.

- Initial bootup of the controller will be at the Cisco Wireless/Cisco DNA Advantage level.

Smart Accounts

A [Smart Account](#) is a central data repository that provides visibility and access control to all the Cisco software licenses and entitlements across an organization. Smart Accounts allow customers to store, manage, and move assets across locations and devices and begin to use them immediately. Smart Accounts are required for enabling Cisco Smart Software Licensing.

After a Smart Account has been set up, customers have the flexibility to create subaccounts (virtual accounts) to help manage licenses for departments, areas, or locations within their organization. Licenses can be pooled within virtual accounts as needed. Smart Accounts support role-based user access controls, which allow the delegation of authority to account administrators at the Smart Account level or at the virtual account level. In addition, customers can assign partner visibility and management rights to their virtual or enterprise-level accounts.

After purchasing a Cisco Catalyst controller up to day 1:

- 1) Create a Smart Account.
 - a) Please use the following link to create a Smart Account:
<https://software.cisco.com/software/company/smartaccounts/home#accountcreation-account>.
 - b) Go to Cisco Software Central at software.cisco.com.
 - c) An editable profile appears.
 - d) An email is automatically sent to the customer Smart Account administrator.
- 2) Register the Cisco Catalyst controller using the Smart Account.

Existing customers:

 - a) Deposit existing Cisco Wireless or Cisco DNA licenses, if any, into the Smart Account.
 - b) Leverage offers to migrate existing perpetual licenses to Cisco DNA licenses.

New customers:

 - a) Purchase Cisco Wireless or Cisco DNA licenses for access points connecting to the Cisco Catalyst controller.
- 3) Configure the license level on the box after bootup.

Additional information

[Operations Exchange](#) site featuring Smart Account overviews and training sessions: Navigate to the Smart Account Resources panel on the page.

Smart Licensing

Unified licensing and Smart Licensing are cloud-based approaches to licensing. The solution simplifies the purchase, deployment, and management of Cisco software assets. Entitlements are immediately deposited into the customer's virtual account for use. This eliminates the need to install license files on every device. Products that are smart enabled communicate with Cisco to report license consumption. The primary location for managing product registration and monitoring Smart License consumption is Meraki Dashboard or the Cisco Smart Software Manager. License ownership and consumption are readily available to help customers make better purchase decisions based on consumption or other business needs.

Smart Licensing for Cisco Catalyst 9800 Series Wireless Controllers is enabled starting with the 16.10.1 release.

Unified licensing for Cisco Catalyst 9800 Series Wireless Controllers is enabled starting with the 17.15.2 release.

Cisco enterprise wireless licenses

Table 64 list the product IDs for ordering Cisco DNA licenses for access points.

Table 64. A la carte part numbers for Cisco DNA for access points

License type	Product ID	Description
A la carte part numbers		
Wireless Cisco DNA Essentials	AIR-DNA-E-3Y (greenfield)	Wireless Cisco DNA Essentials Term License, per AP
	AIR-DNA-E-5Y (greenfield)	Wireless Cisco DNA Essentials 3-year term license, per AP
	AIR-DNA-E-7Y (greenfield)	Wireless Cisco DNA Essentials 5-year term license, per AP Wireless Cisco DNA Essentials 7-year term license, per AP
Wireless Cisco DNA Advantage	AIR-DNA-A-3Y (greenfield)	Wireless Cisco DNA Advantage Term License, per AP
	AIR-DNA-A-5Y (greenfield)	Wireless Cisco DNA Advantage 3-year term license, per AP
	AIR-DNA-A-7Y (greenfield)	Wireless Cisco DNA Advantage 5-year term license, per AP Wireless Cisco DNA Advantage 7-year term license, per AP

Cisco Software-Defined Access (SD-Access)

SD-Access enables policy-based automation from edge to cloud with foundational capabilities using controller-based architecture, including design with validated templates, simplified device deployment, unified management of wired and wireless, network virtualization with segmentation, group-based policies, and context-based analytics.

SD Access can be enabled via Cisco DNA Advantage. The solution needs Cisco Identity Services Engine (ISE) licenses, which can be bought a-la-carte or through the Cisco DNA Expansion Pack. The Cisco DNA Expansion Pack is a flexible way to purchase Cisco ISE, Cisco Spaces, Cisco ThousandEyes, Cisco Secure Network Analytics (Stealthwatch) and other licenses, appliances, and services to enhance your Cisco Networking solutions.

Services

Cisco Support Services

For complex hardware, software, and third-party partner solutions, Cisco Solution Support delivers centralized support across the Cisco and solution partner products in your deployment to resolve complex issues faster. Learn more at [Cisco Solution Support](#).

Cisco Success Tracks is a suite of digital-first services designed to help customers realize the full value of their Cisco investments. It combines Solution Support, access to expertise and contextual learning with use case-guided journeys, and improved visibility through data-driven insights and analytics to conduct more proactive and predictive IT operations and expedite adoption. Learn more at [Cisco Success Tracks](#).

Cisco Software Support included with Cisco DNA license

Cisco Software Support provides access to Cisco Technical Assistance Center (TAC) support, major software updates, and maintenance and minor software releases. It delivers the right support for Cisco software, to help maximize the value derived from the software.

Cisco Network Subscription product support included with unified license

The unified license includes product support for Cisco software and software-managed hardware. It will keep your network performing as expected and protect your investment. Cisco Product Support provides access to Communities, TAC support, major software updates, maintenance and minor software releases, digital insights and e-Learning. See [Service Descriptions](#) for more information.

Cisco RMA upgrade

This RMA hardware replacement service is available for unified license managed products only. There are multiple service levels to choose from. See [Service Descriptions](#) for more information.

Advanced Services

Advanced Services provides expert guidance to plan, design, and implement technology transformations, de-risking transformation and accelerating adoption. Learn more at [Advanced Services](#).

Cisco Lifecycle Services provides expert guidance in optimizing and transforming your network infrastructure to get to business outcomes faster. Learn more at Cisco Lifecycle Services.

Online resources

- Cisco End User License Agreement (EULA)

The Cisco EULA governing software use is available at:

<https://www.cisco.com/go/softwareterms>

- Warranty online

Product warranty terms and other information applicable to Cisco products are available at:

<https://www.cisco.com/go/warranty>

Consult the above website or your Cisco sales and service representative for a complete listing of Cisco products and applicable warranties.

Important links

Smart Accounts: All you need to know

- [Operations Exchange: Partner and distributor software training](#): A comprehensive list of external software training resources. Detailed training modules for ordering and license management.
- [Smart Account Leading Practices for Customers](#): A leading practices guide that can help customers decide how to structure their Smart Accounts or if they need multiple Smart Accounts.
- [Smart Account Decision Tree](#): A short branching survey that helps partners and customers understand what types of Smart Accounts to create.
- [Cisco Smart Accounts site](#): The primary Cisco.com site for Smart Accounts.

Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)