

GCS1602CC

2-Port 4K USB-C Desktop KVM with DisplayPort output and USB peripheral

USB-C KVMP - Switch Between Two USB-C Devices

Easily switch between two USB-C devices and control them with one keyboard, one mouse and view content on one 4K monitor. IOGEAR GCS1602CC requires no software and comes complete with the Power Delivery function, USB-C cables, and a 6-foot push-button remote switch.

Why spend extra money on features you don't need? The USB-C KVM offers the most efficient and affordable way to switch between two USB-C or Thunderbolt™ 3-equipped Mac® computers, PCs, iPad® or Android™ tablets and smartphones with a single-cable connection to each device without additional drivers or software.

Additional USB ports on GCS1602CC allows users to connect to more USB devices, such as USB printer, storage, camera, etc.

Requirements

Package Contents

Specifications

Function	GCS1602CC
Upstream Port	
USB-C	2x USB-C for Laptops; data rate up to 5Gbps
Downstream Port	
DisplayPort	1x DP 1.4 compliant, up to 4k60Hz
USB-A	4x USB-A 3.2 Gen 1, data rate up to 5Gbps
USB-C	1x USB-C for Power Delivery Pass-Thru
Power	
Power Delivery Pass-Thru	Port 1: Supports 100W USB-C PD laptop charging at 5V, 9V, 15V, and 20V output2 Port 2: Supports max. 5V, 3A output
Input Rating	DC12V, 3.3A
Operating System Requirements	
Mac	Mac OS® X 9.0+
Windows	Windows® 10, 11 (32-bit / 64-bit) with 7th-Gen Intel Core Processor or above
Android	Android 8+
iOS	iPadOS 13.1 or later
Environment	
Humidity	0?80% RH, Non-condensing
Operation Temperature	32 - 104°F (0?40°C)
Storage Temperature	-4 - 140°F (-20?60°C)

Dimensions	GCS1602CC
Unit Package Dimensions	
Height	6.8 in. (17.3 cm)
Length	11.2 in (28.3 cm)
Width	2.5 in. (6.2 cm)
Master Carton	
Height	7.6 in. (19.4 cm)
Length	15.8 in. (40.2 cm)
Width	11.8 in. (30 cm)
Master Carton Qty.	6
Weight	
Master Carton Wt.	15.3 lb. (6.9 kg)
Unit Pack Wt.	2.3 lb. (1.02 kg)